

FORMS OF SUPPLY

LAUROCRYL[®] B-505: 60% solids in toluene

LAUROCRYL B-505

TYPE AND USE

Pure acrylic thermoplastic resin. Binder for cement facing substrates, low viscosity primers and penetrating stone varnishes.
Suitable for roadmarking paints.

PRINCIPAL PROPERTIES

Fast drying.
Good permanent flexibility.
Excellent insulating properties.

SOLUBILITY

Aliphatic solvents insoluble
Aromatic hydrocarbons complete
Esters, ketones complete
Alcohols insoluble

TECHNICAL CHARACTERISTICS

Non-volatile content (ELOT EN ISO 3251) 60±1%
Viscosity, 60% in toluene
 25°C (ELOT EN ISO 2884) mPa.s 3.000 - 9.000
Acid value (ELOT EN ISO 3682 on n.v.) 7 max
Colour, 50% nv
 Gardner colour scale (ELOT EN ISO 4630) 2 max

OTHER CHARACTERISTICS (informative)

Flash point approx. 4°C

The information contained herein is provided in good faith and is to the best of our knowledge accurate. Therefore, the buyer is advised to determine the suitability of this product for the intended use. We retain the right to make any changes according to technological progress or further developments. For safety and additional information please refer to the Material Safety Data Sheet as well as to other informative documents accompanying the product.

LAUROCRYL B-505 en
Version 2.0